

# TANK ALERT® EZ (CE) Alarm System

## Innovative, indoor or outdoor liquid level alarm system.

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other water applications.

The **Tank Alert® EZ (CE)** indoor/outdoor alarm can serve as a high or low level alarm depending on the float switch model used. This easy to install alarm features an innovative, 2-color molded enclosure. The top half of the enclosure is translucent and illuminates red when an alarm condition occurs.



## FEATURES

U.S. Patent Nos. 8,737,672 and D695,640

- 2-color molded enclosure offers a distinct look; upper translucent half illuminates in alarm condition.
- Removable lower cover provides greater access for easier field wiring while the internal circuitry remains protected.
- Interlocking enclosure features unique sound chamber to amplify the horn, while helping prevent moisture from entering.
- External mounting tabs for easy installation.
- Enclosure meets Type 3R water-tight standards.
- Enclosure has indicator marks on bottom for easy placement of cord entry locations.
- Automatic alarm reset, horn silence switch, and alarm test switch.
- Alarm horn sounds at 82 decibels at 3 meters (10 feet).
- Alarm system (when installed on separate circuit) operates even if pump circuit fails.
- Green power on indicator.
- Includes auxiliary alarm contacts for easy attachment of remote devices.
- Complete package includes standard SJE SignalMaster® control switch with 4.57 meters (15 feet) of cable (other lengths available) and mounting clamp.



## SPECIFICATIONS

### Voltage:

#### 240 VAC Model:

Primary: 240 VAC, 50/60 Hz, 3.8 watts max. (alarm condition)

Secondary: 9 VDC

**Alarm Enclosure:** 17.02 x 13.46 x 6.35 cm (6.7 x 5.3 x 2.5 inch), indoor-outdoor, weatherproof, thermoplastic meets Type 3R water-tight standard

**Alarm Horn:** 82 decibels at 3 meters (10 feet)

**Auxiliary Alarm Contacts:** 240 VAC / 30 VDC, 1.5 amps max., 50/60 Hz (circuit not supervised)

**Float Switch:** SJE SignalMaster® control switch with mounting clamp

**Cable:** 4.57 meters (15 feet), flexible 18 gauge, 2 conductor (UL) SJOW, water-resistant (CPE)

**Float:** 7 cm diameter x 12.3 cm long (2.74 x 4.83), high impact, corrosion resistant polypropylene housing for use in sewage and non-potable water up to 60°C (140°F)

**Maximum Water Depth:** 9 meters (30 feet), 13 PSI

**Electrical:** 5 amps, 240 VAC, 50/60 Hz



**SJE RHOMBUS™**

PO Box 1708, Detroit Lakes, MN 56502

Phone: +1 218 847 1317

email: [customer.service@sjerhombus.com](mailto:customer.service@sjerhombus.com)

**www.sjerhombus.com C.5**

**SEE BACK SIDE FOR COMPLETE LISTING OF AVAILABLE OPTIONS.**

# TANK ALERT® EZ (CE) Alarm System

Innovative, indoor or outdoor liquid level alarm system.

## NOTE

The Tank Alert® EZ (CE) alarms are manufactured at SJE Rhombus® Suzhou Co. Ltd.  
Contact SJE Rhombus® for pricing or submit an online quote request at [www.sjerhombus.com](http://www.sjerhombus.com).

## ORDERING INFORMATION

STANDARD ALARM (240 VAC)		Shipping Weight
Part #	Description	
<b>1042885</b>	TAEZCE-02H (240 VAC w/SJE SignalMaster® High Level)	1.25 kg
<b>1042886</b>	TAEZCE-02X (240 VAC no float)	0.68 kg

H = High Level L = Low Level X = No Float

MASTER CARTON holds 12 boxed units.

CONTACT CORPORATE FACTORY FOR PRICING.

## OPTIONS

### Control Switch Options:

The Tank Alert® EZ alarm system comes standard with a 4.57 meter (15 ft.) SJE SignalMaster® control switch with mounting clamp. Other float switches are available. See the control switch section of this catalog.



**SJE RHOMBUS**

[www.sjerhombus.com](http://www.sjerhombus.com)

[customer.service@sjerhombus.com](mailto:customer.service@sjerhombus.com)