

ACCESSORIES

Cable Weights, Cable Clamp Assembly, Float Bracket, 4-20mA Simulator

CABLE WEIGHT

Provides an accurate pivot point for suspended floats.

- Gripper teeth on clip and weight channel securely lock float cable into place
- Cable Weight can be adjusted without the use of tools
- Housing: 7.1 cm diameter x 8.4 cm (2.8 inch diameter x 3.3 inch long), impact resistant, non-corrosive, PVC housing for use in liquids up to 60°C (140°F)
- Clip: injection molded acetal plastic



U.S. Patent 5,306,885

Wire/Cable Accommodated: SJOW, SJTW, 18/2, 18/3, 16/2, 16/3, 14/2 and 14/3

Part Number	Description	Ship Weight
1002230	Cable Weight	0.86 kg

CABLE WEIGHT MINI

Provides an accurate pivot point for suspended floats.



- One piece cable weight
- Turn and lock for easy installation
- Housing: 6.35 cm diameter x 6.35 cm long (2.5 inch diameter x 2.5 inch long), impact resistant, non-corrosive, PVC housing for use in liquids up to 60°C (140°F)

Wire/Cable Accommodated: SJOW, SJTW, 18/2, 18/3

Part Number	Description	Ship Weight
1030356	Cable Weight Mini	0.32 kg

CABLE CLAMP ASSEMBLY

Provides cable anchor point and strain relief. Secures cable in vertical direction.



- For use with 18/16 gauge, 14 gauge, & 12 gauge cable
- Mounting clamp: ABS nylon blend
- Hose clamp: highly corrosion resistant stainless steel

Part Number	Description	Ship Weight
1008569	18 & 16 gauge Cable Clamp Assembly	0.09 kg
1008574	14 gauge Cable Clamp Assembly	0.09 kg
1008575	12 gauge Cable Clamp Assembly	0.09 kg



SJE RHOMBUS.

Phone: +1 218 847 1317
email: customer.service@sjeinc.com

www.sjerhombus.com F.3


ACCESSORIES

Cable Weights, Cable Clamp Assembly, Float Bracket, 4-20mA Simulator

FLOAT BRACKET

Provides convenient installation of floats.

- Six Float Bracket supports 1-6 floats
- Four Float Bracket supports 1-4 floats
- Can be directly mounted to wall or used with wall mounting device
- Provides convenient location to stow excess float cord
- Supplied with UL Recognized cord strain relief connectors



Metal Components: all metal components are made of 300 series stainless steel

Strain Relief Connectors: accommodates 18/2, 18/3, 16/2, 16/3 SJOW and SJTW cords

Part Number	Description	Ship Weight
1009432	4 Float Bracket with Mounting Device	1.14 kg
1009433	4 Float Bracket without Mounting Device	1.00 kg
1009434	6 Float Bracket with Mounting Device	1.27 kg
1009435	6 Float Bracket without Mounting Device	1.13 kg
1009436	Float Bracket Mounting Device	0.14 kg

4-20mA SIMULATOR

Easy-to-use, hand-held testing instrument.

- Designed to generate an adjustable 4-20mA signal from loop power
- Output adjusted across the full range by turning the adjustment knob
- Can be used for a wide range of applications, provided the excitation voltage is within 12-24 VDC



Part Number	Description	Ship Weight
1039199	4-20mA Simulator	0.15 kg

SEE INTERNATIONAL PRICE BOOK FOR LIST PRICING.