MODEL PSII/PSI2 Control Panel

Single phase, two independent motor contactor control/programmable timed dosing control panel.

The PS11 (120V) PS12 (240V) control panel provide a reliable means of controlling both pump chamber and sand filter pumps in an onsite septic installation.

PANEL COMPONENTS

- **Enclosure** measures 14 x 12 x 6 inches (35.56 x 30.48 x 15.24 cm); NEMA 4X (ultraviolet stabilized thermoplastic) with removable mounting feet for indoor or outdoor use.
- 2. Pump Chamber Magnetic Motor Contactor controls pump chamber pump by switching electrical lines.
- Sand Filter Magnetic Motor Contactor controls sand filter pump by switching electrical lines.
- Alarm/Control Fuse 4.
- 5. Float Switch Terminal Block
- **Control/Pump Power Terminal Block**
- **Programmable Timer** features separate variable controls to allow for pump chamber pump on/off time settings from .05 seconds to 30 hours.
- Pump Chamber Circuit Breaker provides pump chamber disconnect and provides branch circuit protection.
- Sand Filter Circuit Breaker provides sand filter pump disconnect and provides branch circuit protection.
- 10. HOA Switches provide manual pump control.
- 11. Ground Lugs
- 12. Spare Fuse
- 13. Red Alarm Beacon provides 360° visual check of alarm condition.
- 14. Alarm Horn provides audio warning of alarm condition (83 to 85 decibel rating).
- 15. Exterior Alarm Test/Normal/Silence Switch allows horn and light to be tested and horn to be silenced in an alarm condition. Alarm automatically resets once alarm condition is cleared.
- 16. Horn Silence Relay (mounted under bracket).
- 17. Elapsed Time Meter
- 18. Event Counter


NOTE: Wiring Diagram, Pump Specification Label and Timer Installation Label are located inside the panel on enclosure cover.

FEATURES

- Entire control system (panel and switches) is UL Listed to meet and/or exceed industry safety standards
- Dual safety certification for the United States and Canada
- Standard package includes three 20' SJE PumpMaster® pump switches, one 20' SJE PumpMaster® pump switch, one 20' SJE VerticalMaster® pump switch and one 20' SJE PumpMaster® SPDT pump switch

California Prop 65 requires the following: NWARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov

- Complete with step-by-step installation instructions
- Five-year limited warranty



Model Shown PS12





MODEL PSII/PSI2 Onsite Control Panel

Single phase, two independant motor contactor control/programmable timed dosing control panel.

120 VAC		Shipping
Part #	Description	Weight
1006586	PS11	26 lbs.

240 VAC		Shipping
Part #	Description	Weight
1007395	PS12	26 lbs.

SEE PRICE BOOK FOR LIST PRICE.



SPECIFICATIONS

VOLTAGE: 120 VAC (PS11) or 240 VAC (PS12)

ENCLOSURE: 14 x 10 x 6 inch (35.56 x 30.48 x 15.24 cm)

NEMA 4X weatherproof thermoplastic with hinged door.

BRANCH CIRCUIT PROTECTION: Circuit breakers for pump chamber and sand

filter pumps.



www.sjerhombus.com customer.service@sjeinc.com