

QUICK POST PLUS™ Outdoor System

Easy to install Quick Post Plus™ outdoor system provides convenient wiring connection and system monitoring for pump station applications.

The Quick Post Plus™ outdoor system features an 8 x 8 x 4 inch enclosure with integral alarm and terminals to connect alarm and incoming power. The provided receptacle plug pigtail is available in 120VAC or 230VAC to accept a pump switch piggyback plug, pump plug, and optional ETM. The provided factory-installed 22" weather proof post features access door for easy wiring. The system also includes the riser extension conduit with stainless steel compression nuts to connect the mounting post to the riser, two cord seals, and SJE SignalMaster® control switch.

The post can be mounted directly into the ground, over 4 x 4 inch (10.16 x 10.16 cm) post or over conduit.

FEATURES

- NEMA 4X enclosure with hinged door.
- Factory installed mounting post with access cover for easy wiring.
- Receptacle pigtail (120 VAC or 230 VAC) and wiring terminal blocks for easy field connections.
- Separate alarm and pump control circuit.
- Riser extension 2.5 inch (6.35 cm) diameter coupling conduit to accommodate float piggyback plug.
- Riser extension stainless steel compression nuts provide easy adjustability and strong connection.
- Strain relief for pump and float cords, provided by cord seals.
- Integrated alarm, beacon, horn, and test/silence switch to provide high level alarm notification.
- SJE SignalMaster® control switch provides alarm activation.
- Entire control system (panel and float switch) is UL and cUL Listed to meet and/or exceed industry safety standards.
- Five-year limited warranty.

OPTIONS

- Elapsed Timer Meter provides pump operation timer.
- DUO alarm input to provide high and low level alarm or filter alarm depending on the float switch model used.



Quick Post Plus™ outdoor system with optional elapsed time meter

SPECIFICATIONS

VOLTAGE: 120 VAC or 230 VAC; 50/60hz

ENCLOSURE: 8" x 8" x 4" (20.32 x 20.32 x 10.16 cm), NEMA 4X ultraviolet stabilized thermoplastic

RECEPTACLE PIGTAIL: 120 VAC NEMA 5-15R or 230 VAC NEMA 6-15R; 12.0" (30.48 cm) SJTOW cable

MOUNTING POST: 22" x 7" x 6" (55.88 x 17.78 x 15.24 cm) polyethylene weather proof gray engineered thermal plastic with 5.5" x 6.0" (13.97 x 15.24 cm) access cover

RISER EXTENSION KIT: 2.5" (6.35 cm) diameter schedule 40 conduit, 6" (15.24 cm) in length; (2) stainless steel compression nuts

LIQUID TIGHT CORD SEAL:

Seal - neoprene; washers, nuts and bolts - stainless steel

FLOAT SWITCH: SJE SignalMaster® control switch with mounting clamp

ALARM: 360 degree LED beacon, 95 decibels at 2 feet (60.96 cm) piezo horn



SJE RHOMBUS®

1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: customer.service@sjeinc.com

www.sjerhombus.com

B.69

California Prop 65 requires the following:  WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SEE REVERSE SIDE FOR ORDERING INFORMATION.

QUICK POST PLUS™ Outdoor System

Easy to install Quick Post Plus™ outdoor system provides convenient wiring connection and system monitoring for pump station applications.

120 VAC Part #	Description	List Price	Shipping Weight
1053765	120V QPP1W, Integral Alarm, SJE SignalMaster®	\$524.00	5.4 lbs.
1053766	120V QPP1WE, Elapsed Timer Meter, Integral Alarm, SJE SignalMaster®	\$630.00	5.5 lbs.
1053767	120V QPP1WDE, Elapsed Timer Meter, DUO Alarm, SJE SignalMaster®	\$784.00	5.5 lbs.

230 VAC Part #	Description	List Price	Shipping Weight
1053768	230V QPP2W, Integral Alarm, SJE SignalMaster®	\$535.00	5.4 lbs.
1053769	230V QPP2WE, Elapsed Timer Meter, Integral Alarm, SJE SignalMaster®	\$641.00	5.5 lbs.
1053770	230V QPP2WDE, Elapsed Timer Meter, DUO Alarm, SJE SignalMaster®	\$814.00	5.5 lbs.

SPECIFICATIONS

VOLTAGE: 120 VAC or 230 VAC; 50/60hz

ENCLOSURE: 8" x 8" x 4" (20.32 x 20.32 x 10.16 cm), NEMA 4X ultraviolet stabilized thermoplastic

RECEPTACLE PIGTAIL: 120 VAC NEMA 5-15R or 230 VAC NEMA 6-15R; 12.0" (30.48 cm) SJTOW cable

MOUNTING POST: 22" x 7" x 6" (55.88 x 17.78 x 15.24 cm) polyethylene weather proof gray engineered thermal plastic with 3" x 3" (7.62 x 7.62 cm) access cover

RISER EXTENSION KIT: 2.5" (6.35 cm) diameter schedule 40 conduit, 6" (15.24 cm) in length; (2) stainless steel compression nuts

LIQUID TIGHT CORD SEAL:

Seal - neoprene; washers, nuts and bolts - stainless steel

FLOAT SWITCH: SJE SignalMaster® control switch with mounting clamp

ALARM: 360 degree LED beacon, 95 decibels at 2 feet (60.96 cm) piezo horn



SJE RHOMBUS.

www.sjerrhombus.com
customer.service@sjeinc.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) • Fax 218-847-4617