

# C-Con™ Converter Box

The C-Con™ converter box allows most control panels to utilize the C-Level™ CL40 floatless sensor.

The C-Con™ converts the signal from a C-Level™ CL40 sensor to simulate float levels (up to four floats). Activation levels can be conveniently set and adjusted at the C-Con™ box by using the output dials, eliminating the need to go into the tank to move float tether points. Works well in wastewater pump tanks, confined space applications, and systems with high grease content.

Note: The C-Con™ converter box can be used with most panels using control switches. The C-Con™ converter box is not recommended for use with plunger type panels or intrinsically safe type panels.



## FEATURES

- NEMA 1 rated for indoor use. (Can be mounted in a control panel.)
- Green power on indicator.
- Four independently adjustable output set points at the converter box with red LED status indicators.
- Adjustable pump start/stop and alarm levels from converter box.
- Simulate button for testing proper wiring of outputs.
- Factory-installed output and power wires.
- Works with most simplex or duplex control panels.
- Alternative to mercury float switches.
- Five-year limited warranty.

## OPTIONS

This system is available with:

- C-Level™ CL40 sensor with 4' (1.22 meters) vent tube and 20' (6.09 meters) cable
- C-Level™ CL40 sensor with 4' (1.22 meters) vent tube and 40' (12.18 meters) cable
- C-Level™ CL40 sensor with 8' (2.44 meters) vent tube and 20' (6.09 meters) cable
- C-Level™ CL40 sensor with 8' (2.44 meters) vent tube and 40' (12.18 meters) cable
- Without C-Level™ CL40 sensor

## SPECIFICATIONS

**VOLTAGE:** 120 VAC, 60Hz, 44mA

**OUTPUT CONTACT RATING:** 3 amp, 240 VAC

**ENCLOSURE:** 3 x 4.25 x 1.25 inches (7.62 x 10.79 x 3.81 cm), NEMA 1 thermoplastic



**SJE RHOMBUS**

1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: [customer.service@sjeinc.com](mailto:customer.service@sjeinc.com)

[www.sjerhombus.com](http://www.sjerhombus.com)

California Prop 65 requires the following:  WARNING Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**SEE REVERSE SIDE FOR ORDERING INFORMATION.**

**E.1**

# C-Con™ Converter Box

Converts any float-operated control panel to utilize the C-Level™ floatless sensor.

120 VAC		List Price	Shipping Weight
Part #	Description		
1031031	C-Con™ converter box w/C-Level™ CL40 sensor (4 foot vent tube and 20 foot cable)	\$624.00	3.5 lbs.
1031032	C-Con™ converter box w/C-Level™ CL40 sensor (4 foot vent tube and 40 foot cable)	\$658.00	4.1 lbs.
1031033	C-Con™ converter box w/C-Level™ CL40 sensor (8 foot vent tube and 20 foot cable)	\$630.00	3.82 lbs.
1031034	C-Con™ converter box w/C-Level™ CL40 sensor (8 foot vent tube and 40 foot cable)	\$664.00	4.42 lbs.
1031067	C-Con™ converter box without C-Level™ CL40 sensor	\$306.00	1.08 lbs.

## SPECIFICATIONS

**VOLTAGE:** 120 VAC, 60Hz, 44mA

**OUTPUT CONTACT RATING:** 3 amp, 240 VAC

**ENCLOSURE:** 3 x 4.25 x 1.25 inches (7.62 x 10.79 x 3.81 cm),  
NEMA 1 thermoplastic



**SJE RHOMBUS.**

[www.sjerrhombus.com](http://www.sjerrhombus.com)  
[customer.service@sjeinc.com](mailto:customer.service@sjeinc.com)

**Call or fax your order!**

**1-888-DIAL-SJE (1-888-342-5753) • Fax 218-847-4617**

*Product offering and pricing are subject to change without notice.  
Please visit [www.sjerrhombus.com](http://www.sjerrhombus.com) for the most current information.*