

TANK ALERT® I

Easy-to-Install Indoor Alarm System

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other water applications.

The **Tank Alert® I** alarm can serve as a high or low level alarm depending on the float switch model used.

The alarm horn sounds when a potentially threatening liquid level condition occurs. The horn can be silenced, but the warning light remains on until the condition is remedied. A green "power on" light indicates power to the alarm panel.

FEATURES

- NEMA 1 enclosure, designed for ease of installation, rated for indoor use
- Red "alarm" light, green "power on" light, alarm "test" switch, and horn "silence" switch
- Alarm horn sounds at 82 decibels at 10 feet (3 meters)
- Can be use with any UL Listed / Recognized switching mechanism rated to include 1 amp, 12 VAC load
- Alarm system (when installed on separate circuit) operates even if the pump circuit fails
- Complete package includes SJE SignalMaster® control switch with 15 feet of cable
- Switching mechanism operates on low voltage and is isolated from power line to reduce possibility of shock
- Alternate float switch models for high or low level warning
- 230V models available

PART NO. DESCRIPTION

- **1007457** TAI-01H 15' SJE SignalMaster® High Level
- **1009207** TAI-01HSPKT, 15' SJE SignalMaster® High Level with Splice Kit
- **1003104** TAI-01H, 15' Sensor Float® High Level
- **1003365** TAI-01L, 15' Sensor Float® Low Level
- **1002235** TAI-01X, no float

