

XPERT ALERT® WiFi INDOOR ALARM SYSTEM

The Xpert Alert® WiFi indoor alarm system helps protect your home 24/7 from potentially costly damage due to flooding, pump failure or freezing pipes. The system monitors and reports any residential alarm condition by notifying you locally (audible and visual alarms) and remotely via SMS text messages and/or emails over a WiFi or Ethernet network to your smartphone, tablet or computer. The sleek design of the enclosure, with its unique shape, smooth rounded edges, and large push button with LED light ring, makes this attractive alarm ideal for residential applications.

When the tank level rises, the high water float activates the alarm to audibly and visually warn of potentially threatening liquid level conditions. The alarm features an easy-to-see LED alarm light ring that illuminates red for alarm 1 and amber for alarm 2. The alarm horn can be silenced by pressing the large button, but the LED remains on as long as the alarm condition exists. Once the condition is cleared, the alarm automatically resets. A red "Low Temperature" LED activates when the temperature falls below 4°C (40°F) to help protect against freezing pipes; this can be disabled for installations in cold areas. When alarm conditions occur, you are notified by text/email message.

The alarm works with your existing WiFi or Ethernet network. Since it does not rely on a cellular connection, it is an excellent solution for areas with poor cellular service. No monthly fees or contracts! Easy installation and setup make this a great option for businesses, rental properties and seasonal homes to help prevent costly damage.

FEATURES

- NEMA 1 enclosure rated for indoor use
- 2 sensor inputs to monitor 2 separate alarm conditions
- LED alarm light ring alerts you of alarm status; red for alarm 1, amber for alarm 2
- Audible alarm activates for alarm 1, alarm 2, low temperature and low battery chirp
- LED power indicators (green = primary power, amber = battery backup, red = low battery)
- LED network status indicator (blue flashing = network connection setup, blue constant = network connection established)
- Text and/or email notifications: alarm, power lost, power restored, low temperature, low battery and alarm offline
- Notifies up to 4 contacts (2 email and 2 text, **text in country code 1 only**, maximum of 10 text messages sent per day)
- Simple Access Point Mode push-button WiFi connection (or Ethernet)
- Large, easy-to-use test/silence push-button located conveniently on front of alarm
- Includes auxiliary contacts for attachment of remote devices (continues to operate during loss of power)
- Automatic alarm reset and integral rechargeable battery backup

SPECIFICATIONS

VOLTAGE:

Primary: 120 VAC, 60 Hz, 5 watts max. (alarm condition)
Secondary: 5 VDC

BATTERY BACKUP POWER: 3.7 VDC rechargeable lithium

ALARM ENCLOSURE: 14 x 10 x 4.5 cm (5.5 x 4 x 1.75 inch), NEMA 1 plastic.

ALARM HORN: 80 decibels at 3 meters (10 feet)

POWER CORD: 1.8 meter (6 foot) MicroUSB

FLOAT SWITCH CONNECTION TERMINALS:

For float switch connection only - do not apply power. (Voltage across terminals is 3 VDC).

FLOAT SWITCH: SJE MilliAmpMaster™ control switch with mounting clamp

Cable: 3 meters (10 feet), flexible 18 gauge, 2 conductor (UL) SJOW, water-resistant (CPE)

Float: 7.0 cm x 12.3 cm long (2.74 inch diameter x 4.83 inch long), high impact, corrosion resistant polypropylene housing for use in sewage and water up to 60°C (140°F)

WIFI: Connect using Access Point Mode or manually by using Ethernet connection (ethernet cable not provided). WPA2 security required on wireless router.

ETHERNET: Requires an ethernet connection (ethernet cable not provided).

NOTE: Cellular WiFi hotspots are not recommended for use with this WiFi alarm, as intermittent or unreliable notification service can result.

AUXILIARY ALARM CONTACTS: Normally open, normally closed (CSA certified)

Voltage: ≤ 30 VAC/VDC (Class 2)

Current: 1 amp maximum

SEE BACK SIDE FOR COMPLETE LISTING OF AVAILABLE OPTIONS.



Patent Pending



SJE RHOMBUS

Phone: +1 218 847 1317
email: customer.service@sjeinc.com

www.sjerhombus.com C.3

XPERT ALERT® WIFI INDOOR ALARM SYSTEM

Easy-to-install indoor alarm system with WiFi connectivity, remote notification, 2 alarm inputs, temperature alarm, auto reset and battery backup.

ORDERING INFORMATION

STANDARD ALARM (120 VAC)		Shipping Weight
Part #	Description	
1060316	Xpert Alert® WiFi, 120V, High w/ 10' SJE MilliAmpMaster™ Float	0.84 kg
1061894	Xpert Alert® WiFi, 120V, no float	0.39 kg

MASTER CARTON holds 16 boxed units.

SEE PRICE BOOK FOR LIST PRICE.

OPTIONS

CONTROL SWITCH OPTIONS

The Xpert Alert® WiFi alarm system comes standard with a 3 meter (10ft) **SJE MilliAmpMaster™** control switch with mounting clamp. Other float switches may be ordered separately. See control switch section of the catalog.



SJE RHOMBUS

www.sjerhombus.com

customer.service@sjeinc.com

9500459A 10/19

© 2019 SJE, Inc. All Rights Reserved.
SJE RHOMBUS is a trademark of SJE, Inc.