

# RAPID SET™ SYSTEM

## Ready to Install Lift Station Control Package

### Current Installations



### Rapid Set Installation



Patent: D963,196S

The Rapid Set™ mounting system provides a complete, ready to install lift station control package. No more need for extra tools, supplies, or people to build and mount controls! The welded stainless steel frame provides a durable, yet clean, controls package for fast installation. The sunshield provides operators and controls protection from the weather. The additional mounting plate of the Rapid Set system allows for operators to easily install any additional controls that the station may need or contact us about having these components factory installed prior to shipment for even faster system installation!

### FEATURES

- Reduce on-site installation time
- Consistent appearance to installation
- Compact footprint
- Stainless steel construction to prevent corrosion
- Control panel factory installed
- Additional mounting space for other electrical components
- Standard 122 mph wind rating
- Optional design for 200 mph wind rating
- Sloped top acts as a sunshield and protects equipment and operators from weather
- 2-year limited warranty



9500606A Rev 11/24  
© 2024 SJE, Inc. All Rights Reserved.  
SJE RHOMBUS is a trademark of SJE, Inc.

[www.sjerhombus.com](http://www.sjerhombus.com)   Toll Free 888-342-5753   Phone 218-847-1317

# RAPID SET™ SYSTEM

## Ready to Install Lift Station Control Package

### SPECIFICATIONS

**FRAME:** Welded 2" square tubing frame, 304 stainless steel

**SUNSHIELD:** Welded 0.125" thick 5052 aluminum

**DISCONNECT MOUNTING PLATE:** 0.125" thick 5052 aluminum  
(for mounting meter,  
disconnect, accessories)

**JBOX MOUNTING BRACKETS:** 0.125" thick 5052 aluminum  
(for mounting junction box,  
conduit support, etc.)

**FINISH:** Powder Coated White

**FRAME FASTENERS:** Grade 8 per SAE J429, Fastener Finish -  
EcoGuard®, Fastenal Product Standard:  
C.1000.ECO

#### CONTROL PANEL SIZES:

- 36" x 36" - mounts directly to SS frame  
(predrilled holes)
- 36" x 30" - mounts directly to SS frame  
(predrilled holes)
- Additional mounting plate available for smaller size panels

**LIFTING EYES:** Designed for 700 lbs. total max weight

- Control panel must not exceed 400 lbs.
- Service disconnect/meter/accessories must not exceed 140 lbs.

### 122 MPH WIND RATING

**CONCRETE BALLAST SUGGESTED SIZE:** 5' 0" x 5' 0" x 1'0"

- Minimum 4,000 psi concrete

### **ANCHOR BOLTS MINIMUM REQUIREMENTS:**

- ICC approved 0.5" diameter wedge anchors
- Minimum tension capacity of 3,000 pounds
- 3.25" minimum embedment into concrete

**CONTROL PANEL:** 400 lbs. max. weight allowed for rating

**MOUNTING PLATE COMPONENTS:** 100 lbs. max weight allowed  
for rating

**JUNCTION BOX:** 40 lbs. max. weight

\*A qualified professional engineer must verify the foundation  
adequacy for specific site conditions prior to installation.

### 200 MPH WIND RATING

**CONCRETE BALLAST SUGGESTED SIZE:** 6' 0" x 6' 0" x 2' 0"

- Minimum 4,000 psi concrete

### **ANCHOR BOLTS MINIMUM REQUIREMENTS:**

- ICC approved 0.5" diameter wedge anchors
- Minimum tension capacity of 3,000 lbs.
- 3.25" minimum embedment into concrete

**CONTROL PANEL:** 400 lbs. max. weight allowed for rating

**MOUNTING PLATE COMPONENTS:** 100 lbs. max weight allowed  
for rating

**JUNCTION BOX:** 40 lbs. max. weight

\*A qualified professional engineer must verify the foundation  
adequacy for specific site conditions prior to installation.

### ACCESSORIES

Optional mounting adapter plate – for smaller enclosures



**SJE RHOMBUS**<sup>®</sup>