


INSTALLER FRIENDLY SERIES® (IFS)

THREE PHASE SIMPLEX

Demand Dose or Timed Dose, Float, Sensor or Transmitter Controlled System for Pump Control and System Monitoring



Panel layout may vary with options. Reg. Cdn Pat. & TM Off
US Patent No. 8,336,385; 8,567,242; 8,650,949

Installer Friendly Series®

The Next Generation IFS simplex control panel utilizes an innovative circuit board design enclosed in a touch-safe housing to control one 208/240/480 and 600 VAC three phase pump in water and sewage applications. These newly redesigned IFS panels feature an easy-to-use color LCD interface located on the inner door for programming and system monitoring. The panel configuration can be easily converted in the field to either a timed dose or demand dose through the LCD interface.

The panel can easily be changed in the field to utilize floats, Sub-X™ LT Transmitter or the C-Level™ Sensor for continuous level monitoring. The Sub-X™ LT Transmitter and the C-Level™ Sensor sense the level in the tank and sends a signal to the panel. Pump activation levels can be adjusted by using the LCD interface.

- Five-year limited warranty on panel
- Two-year limited warranty on C-Level™ Sensor and Sub-X™ LT Transmitter

LCD INTERFACE FEATURES

- Full color graphics and menu navigation encoder for easy setup
- Touch safe housing
- Pump Hand/Off/Auto Control selectable via menu navigation
- Sub-X™ LT Transmitter, C-Level™ Sensor or float operation selectable
- Demand or Timed Dose operation selectable via menu navigation
- Tank Level Indication and setpoint monitoring at-a-glance
- Lead pump is easily identified by a graphic ring around the current lead pump regardless of control mode (timed dose or demand)
- Displays remaining time in Timed Dose mode
- RJ45 communication connector
- Flashing function for alarm beacon and horn (configurable)
- Manual alarm reset (configurable)
- Thermal cutout and seal failure module (optional)

COMPONENTS

1. Enclosure base measures 14 x 12 x 6 inches (35.56 x 30.48 x 15.24 cm); NEMA 4X (ultraviolet stabilized thermoplastic)
2. Red Alarm Beacon provides 360° visual check of alarm condition
3. Motor protective switches provide adjustable overload, branch circuit protection and pump disconnect
4. IEC motor contactors control pumps by switching electrical lines
5. Multi-tap transformer (208/240/480 VAC primary) provides 120 VAC control alarm voltage or 600 VAC primary transformer
6. Sub-X™ LT Transmitter, C-Level™ Sensor and float connection terminal blocks
7. Controller Features:
 - a. Incoming Control/Alarm Power terminal blocks
 - b. Control/Alarm Power/System Status green LED indicators illuminate if control/alarm power is present and controller is operating*
 - c. Controller status green LED indicators for: Power/Active, Float Input Status, Pump Run, C-Level Active*
 - d. Normally open auxiliary alarm contacts included as standard
 - e. Control Power On/Off switch
 - f. Green LED Pump Run indicators illuminate when pump is called to run*
 - g. Control panel able to operate if LCD interface fails or is disconnected
 - h. Touch safe housing
8. Modbus Port (RJ45) for future expansion - eg. remote monitoring, valve control, In-Site®, logging, etc.
9. Option 5AE - Thermal Cutout/Heat Sensor & Seal Failure Module
10. Large incoming power connection terminal block
11. Alarm Horn provides audible warning of alarm condition (Not shown)
12. Exterior Alarm Test/Silence push button allows horn and light to be tested and horn to be silenced in an alarm condition; alarm automatically resets once alarm condition is cleared (Not shown)

*In fault condition, LED indicators will be red.

Note: Options, voltage, and amp range selected may change enclosure size and component layout.

Note: Schematic/Wiring Diagram and Pump Specification Label are located inside the panel.



IFN CONTROL PANEL	5 MODEL TYPE	1 ALARM PACKAGE	W ENCLOSURE RATING	PUMP FULL LOAD AMPS	LEVEL CONTROL APPLICATION	6A8AC10E OPTIONS (LISTED BELOW)
-----------------------------	------------------------	---------------------------	------------------------------	----------------------------	----------------------------------	---

CONTROL PANEL	✓	IFN							
MODEL TYPE	✓	5	Three Phase Simplex (includes Option 6A, 8AC and 10E as standard)						
ALARM PACKAGE	✓	1	Alarm Package (includes test/silence switch, red light, & horn)						
ENCLOSURE RATING	✓	W	Weatherproof, NEMA 4X (engineered thermoplastic)						
PUMP FULL LOAD AMPS	208/240/480V		600V						
	001	1.0 - 1.6 FLA	005	1.0 - 1.6 FLA					
	101	1.6 - 2.5 FLA	105	1.6 - 2.5 FLA					
	201	2.5 - 4.0 FLA	205	2.5 - 4.0 FLA					
	301	4.0 - 6.3 FLA	305	4.0 - 6.3 FLA					
	401	6.0 - 10.0 FLA	405	6.0 - 10.0 FLA					
	511	9.0 - 14.0 FLA	515	9.0 - 14.0 FLA					
	611	13.0 - 18.0 FLA	615	13.0 - 18.0 FLA					
	621	17.0 - 23.0 FLA	625	17.0 - 23.0 FLA					
	701	20.0 - 25.0 FLA	705	20.0 - 25.0 FLA					
LEVEL CONTROL APPLICATION	H	Floats - Pump Down (select Option 17 below) Timed dose = redundant off, timer enable, alarm / Demand dose = stop, start, alarm (all systems will ship with 3 floats by default)							
	E	EZconnex® Float Switch System							
	X	No Floats, Transmitter or Sensor							
	C	C-Level™ Sensor (select Option 24 or 29)* Select Option 3E and/or 4D for high water alarm and/or redundant off floats							
	T	Sub-X™ LT Transmitter (select Option 31).* Select Option 3E and/or 4D for high water alarm and/or redundant off floats.							

PRICING WORKSHEET

IFS Three Phase Simplex Base Price _____
 Alarm Package _____
 Enclosure Rating _____
 Pump Full Load Amps _____
 Level Control Application _____
 Total Options _____
TOTAL LIST PRICE _____

***NOTE:** When using the Sub-X™ LT Transmitter or C-Level™ Sensor: Operation is for Pump down applications only.

Industry practices suggest that a secondary device, such as a float switch, be used for redundant activation of the high level alarm and pump shut off.

OPTIONS		DESCRIPTION
3E		High Water Alarm Float (must also select Option 17)** Only Available with Level Control Application = C or T
4D		Redundant Off Float (must also select Option 17)** Only Available with Level Control Application = C or T
5AE		Thermal Cutout/Heat Sensor & Seal Failure Circuit (2 wire)
✓ 6A		Auxiliary Alarm Contact, Form A (included as standard)
✓ 8AC		Display Board - Includes: ETM Counter, Events (Cycles) Counter, Alarm Counter, and Override Counter (Timed Dose Only) (included as standard)
✓ 10E		Lockable Latch - NEMA 4X (included as standard)
10G		Lightning Arrestor
10K		Anti-condensation Heater
16C		30' Cord in Lieu of 20' Cord (per Float)
16D		40' Cord in Lieu of 20' Cord (per Float)
16E		50' Cord in Lieu of 20' Cord (per Float)
16G		100' Cord in Lieu of 20 Cord (per Float)
17C		Sensor Float® / Internally Weighted (3 Floats) - Mercury**
17D		Sensor Float® / Externally Weighted (3 Floats) - Mercury**

OPTIONS		DESCRIPTION
17G		SJE MilliAmpMaster™ / Pipe Clamp (3 Floats) - Mechanical**
17H		SJE MilliAmpMaster™ / Externally Weighted (3 Floats) - Mechanical**
17J		Sensor Float® / Pipe Clamp (3 Floats) - Mercury**
19F		4th Float for Timer Override Only Available with Level Control Application = H
24E		C-Level™ CL40 Sensor with 25' Vented Cable
24F		C-Level™ CL40 Sensor with 50' Vented Cable
24P		C-Level™ CL40 Sensor with 100' Vented Cable
29A		C-Level™ CL100 Sensor with 25' Vented Cable
29B		C-Level™ CL100 Sensor with 50' Vented Cable
29C		C-Level™ CL100 Sensor with 100' Vented Cable
31A		Sub-X™ LT Transmitter 25' (4-20mA)
31B		Sub-X™ LT Transmitter 50' (4-20mA)
31C		Sub-X™ LT Transmitter 100' (4-20mA)
33D		EZconnex® 3-Port, 25', with 10' Floats (3) / Pipe Clamp
35D		EZconnex® 4-Port, 25', with 10' Floats (4) / Pipe Clamp

**For 3E and 4D options, there is no charge when selecting any of the 17 options.

For additional level control and control panel options, please contact Technical Support at techsupport@sjeinc.com.

Note: Added options, voltage, and amp range selected may change enclosure size and enclosure features, and component layout. Schematic/Wiring Diagram and Pump Specification Label are located inside the panel.

SENSOR/TRANSMITTER	OPERATING RANGE
C-Level™ CL40	0-39.9 inWC
C-Level™ CL100	0-99.9 inWC
Sub-X™ LT Transmitter (4-20mA)	0-100 inWC