

QUICK POST PLUS™ SYSTEM WITH INDOOR ALARM

Provides Convenient Wiring Connection and System Monitoring for Pump Station Applications

Plunger Products

The Quick Post Plus™ system features an 8 x 8 x 4 inch enclosure to connect alarm wiring and incoming power. The provided pump switch receptacle plug pigtail is available in 120 VAC or 230 VAC to accept a piggy-back plug, pump plug, and optional elapsed time meter (ETM). The provided factory-installed 22" weatherproof post features access door for easy wiring. The system also includes the riser extension conduit with stainless steel compression nuts to connect the mounting post to the riser, two cord seals, tank alarm, and SJE SignalMaster® control switch.

The post can be mounted directly into the ground, over 4" x 4" (10.16 x 10.16 cm) post or over conduit.

FEATURES

- NEMA 4X enclosure with hinged door
- Factory installed mounting post with access cover for easy wiring
- Receptacle pigtail (120 VAC or 230 VAC) and wiring terminal blocks for easy field connections
- Separate alarm and pump control circuit
- Riser extension 2.5 inch (6.35 cm) diameter coupling conduit to accommodate float piggyback plug
- Riser extension stainless steel compression nuts provide easy adjustability and strong connection
- Strain relief for pump and float cords, provided by cord seals
- Indoor Tank Alert® AB alarm provides high level alarm notification
- SJE SignalMaster® control switch provides alarm activation

OPTIONS

- Elapsed Timer Meter provides pump operation timer
- The Tank Alert® AB DUO alarm system can serve as high or low level alarm or filter alarm depending on the float switch model used
- Xpert Alert® WiFi alarm provides remote alarm notification



Quick Post Plus™ system shown with optional elapsed time meter



Panel layout may vary with options.



QUICK POST PLUS™ SYSTEM WITH INDOOR ALARM - Easy to install Quick Post Plus™ system with indoor alarm provides convenient wiring connection and system monitoring for pump station applications.

Part #	Description (120V)	Shipping Weight
1053759	120V QPP1, Tank Alert® AB, SJE SignalMaster®	5.9 lbs.
1053760	120V QPP1E, Elapsed Timer Meter, Tank Alert® AB, SJE SignalMaster®	6.0 lbs.
1053761	120V QPP1DE, Elapsed Timer Meter, Tank Alert® AB DUO, SJE SignalMaster®	6.0 lbs.
1059013	120V QPP1WiFi, Xpert Alert® WiFi, SJE SignalMaster®	5.91 lbs.
Part #	Description (230V)	Shipping Weight
1053762	230V QPP2, Tank Alert® AB, SJE SignalMaster®	5.9 lbs.
1053763	230V QPP2E, Elapsed Timer Meter, Tank Alert® AB, SJE SignalMaster®	6.0 lbs.
1053764	230V QPP2DE, Elapsed Timer Meter, Tank Alert® AB DUO, SJE SignalMaster®	6.0 lbs.

SPECIFICATIONS

VOLTAGE: 120 VAC or 230 VAC; 50/60hz

ENCLOSURE: 8" x 8" x 4" (20.32 x 20.32 x 10.16 cm)
NEMA 4X ultraviolet stabilized thermoplastic

RECEPTACLE PIGTAIL: 120 VAC NEMA 5-15R or 230 VAC NEMA 6-15R;
12.0" (30.48 cm) SJTOW cable

MOUNTING POST: 22" x 7" x 6" (55.88 x 17.78 x 15.24 cm) polyethylene
weatherproof gray engineered thermal plastic with
3" x 3" (7.62 x 7.62 cm) access cover

RISER EXTENSION KIT: 2.5" (6.35 cm) diameter schedule 40 conduit,
6" (15.24 cm) in length; (2) stainless steel
compression nuts

LIQUID TIGHT CORD SEAL: Seal - neoprene; washers, nuts and bolts -
stainless steel

FLOAT SWITCH: SJE SignalMaster® control switch with mounting clamp

ALARM: Indoor Tank Alert® AB alarm system, Tank Alert® AB DUO alarm
system, or Xpert Alert® WiFi indoor alarm system