


INSTALLER FRIENDLY SERIES® (IFS)

THREE PHASE DUPLEX

Demand Dose or Timed Dose, Float, Sensor or Transmitter Controlled System for Pump Control and System Monitoring



Panel layout may vary with options. Reg. Cdn Pat. & TM Off
US Patent No. 8,336,385; 8,567,242; 8,650,949



Installer Friendly Series®

The Next Generation IFS duplex control panel utilizes an innovative circuit board design enclosed in a touch-safe housing to control two 208/240/480 and 600 VAC three phase pumps in water and sewage applications. These newly redesigned IFS panels feature an easy-to-use color LCD interface located on the inner door for programming and system monitoring. The panel configuration can be easily converted in the field to either a timed dose or demand dose through the LCD interface.

The panel can easily be changed in the field to utilize floats, Sub-X™ LT Transmitter or the C-Level™ Sensor for continuous level monitoring. The Sub-X™ LT Transmitter and the C-Level™ Sensor sense the level in the tank and sends a signal to the panel. Pump activation levels can be adjusted by using the LCD interface.

- Five-year limited warranty on panel
- Two-year limited warranty on C-Level™ Sensor and Sub-X™ LT Transmitter

LCD INTERFACE FEATURES

- Full color graphics and menu navigation encoder for easy setup
- Touch safe housing
- Pump Hand/Off/Auto Control selectable via menu navigation
- Sub-X™ LT Transmitter, C-Level™ Sensor or float operation selectable
- Demand or Timed Dose operation selectable via menu navigation
- Tank Level Indication and setpoint monitoring at-a-glance
- Lead pump is easily identified by a graphic ring around the current lead pump regardless of control mode (timed dose or demand)
- Displays remaining time in Timed Dose mode
- RJ45 communication connector
- Flashing function for alarm beacon and horn (configurable)
- Manual alarm reset (configurable)
- Thermal cutout and seal failure module (optional)

COMPONENTS

1. Enclosure base measures 16 x 14 x 6 inches (40.64 x 35.56 x 15.24 cm); NEMA 4X (ultraviolet stabilized thermoplastic)
2. Red Alarm Beacon provides 360° visual check of alarm condition
3. Motor protective switches provide adjustable overload, branch circuit protection and pump disconnect
4. IEC motor contactors control pumps by switching electrical lines
5. Multi-tap transformer (208/240/480 VAC primary) provides 120 VAC control alarm voltage or 600 VAC primary transformer
6. Sub-X™ LT Transmitter, C-Level™ Sensor and float connection terminal blocks
7. Controller Features:
 - a. Incoming Control/Alarm Power terminal blocks
 - b. Control/Alarm Power/System Status green LED indicators illuminate if control/alarm power is present and controller is operating*
 - c. Controller status green LED indicators for: Power/Active, Float Input Status, Pump Run, C-Level Active*
 - d. Normally open auxiliary alarm contacts included as standard
 - e. Control Power On/Off switch
 - f. Green LED Pump Run indicators illuminate when pump is called to run*
 - g. Control panel able to operate if LCD interface fails or is disconnected
 - h. Touch safe housing
8. Modbus Port (RJ45) for future expansion - eg. remote monitoring, valve control, In-Site®, logging, etc.
9. Option 5AE - Thermal Cutout/Heat Sensor & Seal Failure Module
10. Large incoming power connection terminal block
11. Alarm Horn provides audible warning of alarm condition (Not shown)
12. Exterior Alarm Test/Silence push button allows horn and light to be tested and horn to be silenced in an alarm condition; alarm automatically resets once alarm condition is cleared (Not shown)

*In fault condition, LED indicators will be red.

Note: Options, voltage, and amp range selected may change enclosure size and component layout.

Note: Schematic/Wiring Diagram and Pump Specification Label are located inside the panel.



IFN CONTROL PANEL	6 MODEL TYPE	1 ALARM PACKAGE	W ENCLOSURE RATING	PUMP FULL LOAD AMPS	LEVEL CONTROL APPLICATION	6A8AC10E OPTIONS (LISTED BELOW)
CONTROL PANEL	✓ IFN					
MODEL TYPE	✓ 6	Three Phase Duplex (includes Option 6A, 8AC and 10E as standard)		\$3,102.36		
ALARM PACKAGE	✓ 1	Alarm Package (includes test/silence switch, red light, & horn)		Base		
ENCLOSURE RATING	✓ W	Weatherproof, NEMA 4X (engineered thermoplastic)		Base		
		208/240/480V	600V			
PUMP FULL LOAD AMPS	001	1.0 - 1.6 FLA	005	1.0 - 1.6 FLA	Base	
	101	1.6 - 2.5 FLA	105	1.6 - 2.5 FLA	Base	
	201	2.5 - 4.0 FLA	205	2.5 - 4.0 FLA	Base	
	301	4.0 - 6.3 FLA	305	4.0 - 6.3 FLA	Base	
	401	6.0 - 10.0 FLA	405	6.0 - 10.0 FLA	Base	
	511	9.0 - 14.0 FLA	515	9.0 - 14.0 FLA	\$86.52	
	611	13.0 - 18.0 FLA	615	13.0 - 18.0 FLA	\$86.52	
	621	17.0 - 23.0 FLA	625	17.0 - 23.0 FLA	\$114.33	
	701	20.0 - 25.0 FLA	705	20.0 - 25.0 FLA	\$114.33	
LEVEL CONTROL APPLICATION	H	Floats - Pump Down (select Option 17 below) Timed dose = redundant off, timer enable, alarm / Demand dose = stop, start, alarm (all systems will ship with 3 floats by default)		See Options		
	E	EZconnex® Float Switch System		See Options		
	X	No Floats, Transmitter or Sensor		Base		
	C	C-Level™ Sensor (select Option 24 or 29)* Select Option 3E and/or 4D for high water alarm and/or redundant off floats		See Options		
	T	Sub-X™ LT Transmitter (select Option 31).* Select Option 3E and/or 4D for high water alarm and/or redundant off floats.		See Options		

PRICING WORKSHEET

IFS Three Phase Duplex Base Price	\$3,102.36
Alarm Package	
Enclosure Rating	
Pump Full Load Amps	
Level Control Application	
Total Options	
TOTAL LIST PRICE	

***NOTE:** When using the Sub-X™ LT Transmitter or C-Level™ Sensor: Operation is for Pump down applications only.

Industry practices suggest that a secondary device, such as a float switch, be used for redundant activation of the high level alarm and pump shut off.

OPTIONS	DESCRIPTION	LIST PRICE
3E	High Water Alarm Float (must also select Option 17)** Only Available with Level Control Application = C or T	\$40.17
4D	Redundant Off Float (must also select Option 17)** Only Available with Level Control Application = C or T	\$40.17
5AE	Thermal Cutout/Heat Sensor & Seal Failure Circuit (2 wire)	\$322.39
✓ 6A	Auxiliary Alarm Contact, Form A (included as standard)	\$0.00
✓ 8AC	Display Board - Includes: ETM Counter, Events (Cycles) Counter, Alarm Counter, and Override Counter (Timed Dose Only) (included as standard)	\$0.00
✓ 10E	Lockable Latch - NEMA 4X (included as standard)	\$0.00
10G	Lightning Arrestor	\$309.00
10K	Anti-condensation Heater	\$149.35
16C	30' Cord in Lieu of 20' Cord (per Float)	\$8.24
16D	40' Cord in Lieu of 20' Cord (per Float)	\$16.48
16E	50' Cord in Lieu of 20' Cord (per Float)	\$24.72
16G	100' Cord in Lieu of 20 Cord (per Float)	\$65.92
17C	Sensor Float® / Internally Weighted (3 Floats) - Mercury**	\$170.10
17D	Sensor Float® / Externally Weighted (3 Floats) - Mercury**	\$176.40

OPTIONS	DESCRIPTION	LIST PRICE
17G	SJE MilliAmpMaster™ / Pipe Clamp (3 Floats) - Mechanical**	\$120.51
17H	SJE MilliAmpMaster™ / Externally Weighted (3 Floats) - Mechanical**	\$148.32
17J	Sensor Float® / Pipe Clamp (3 Floats) - Mercury**	\$144.90
19F	4th Float for Timer Override Only Available with Level Control Application = H	\$40.17
24E	C-Level™ CL40 Sensor with 25' Vented Cable	\$341.25
24F	C-Level™ CL40 Sensor with 50' Vented Cable	\$393.75
24P	C-Level™ CL40 Sensor with 100' Vented Cable	\$498.75
29A	C-Level™ CL100 Sensor with 25' Vented Cable	\$393.75
29B	C-Level™ CL100 Sensor with 50' Vented Cable	\$393.75
29C	C-Level™ CL100 Sensor with 100' Vented Cable	\$498.75
31A	Sub-X™ LT Transmitter 25' (4-20mA)	\$334.75
31B	Sub-X™ LT Transmitter 50' (4-20mA)	\$386.25
31C	Sub-X™ LT Transmitter 100' (4-20mA)	\$489.25
33D	EZconnex® 3-Port, 25', with 10' Floats (3) / Pipe Clamp	\$350.27
35D	EZconnex® 4-Port, 25', with 10' Floats (4) / Pipe Clamp	\$424.73

**For 3E and 4D options, there is no charge when selecting any of the 17 options.

For additional level control and control panel options, please contact Technical Support at techsupport@sjeinc.com.

Note: Added options, voltage, and amp range selected may change enclosure size and enclosure features, and component layout. Schematic/Wiring Diagram and Pump Specification Label are located inside the panel.

SENSOR/TRANSMITTER	OPERATING RANGE
C-Level™ CL40	0-39.9 inWC
C-Level™ CL100	0-99.9 inWC
Sub-X™ LT Transmitter (4-20mA)	0-100 inWC