


# MODEL 324 CONTROL PANEL

Three Phase, Duplex Alternating Pump Control with Intrinsically Safe Circuits



Panel layout may vary with options.

The Model 324 control panel is designed to control two 208/240/480 VAC three phase pumps for applications requiring intrinsically safe float circuits. The controller is provided with a pump selector switch that can be set to alternate the pumps to equalize wear or to call either pump to activate first with the other pump to activate in lag condition. If an alarm occurs, the alarm activates the audible-visual system. The alarm conditions include: high water, float out-of-sequence, pump fail-to-run, seal failure (optional). Common applications include pump chambers, lift stations, or other installations classified as hazardous locations requiring intrinsically safe circuits. This panel is available with optional EZconnex® float connection system.

Other features include:

- Touch safe circuit board housing and low voltage float circuits
- Constant alarm (field programmable to flash)
- Alarm automatic reset (field programmable to manual alarm reset)
- Float out-of-sequence detection with automatic float reassignment
- Pump fail-to-run detection (field programmable to deactivate)
- Controller protected by four auto resettable fuses, no fuse replacement
- Three second lag pump delay time, prevents simultaneous pump start-up

## COMPONENTS

1. Enclosure measures 16 x 14 x 6 inches (40.64 x 35.56 x 15.24 cm) NEMA 4X (ultraviolet stabilized thermoplastic with removable mounting feet for outdoor or indoor use)
2. Intrinsically safe module limits the amount of energy to switches preventing ignition of flammable gases
3. Motor protective switches provide adjustable overload, branch circuit protection and pump disconnect
4. IEC motor contactors control pumps by switching electrical lines
5. Multi-tap transformer (208/240/480 VAC primary or 600 VAC primary transformer) provides 120 VAC control/alarm voltage
6. Duplex controller provides pump control, alternation and alarm
  - a. HOA switches for manual control Hand/Off/Automatic
  - b. Control power ON/OFF switch
  - c. Power ON green LED indicator
  - d. Float status red LED indicators
  - e. Float push-to-test buttons
  - f. Pump selector switch: Alt, 1-lead 2-lag, 2-lead 1 lag
  - g. Auxiliary alarm contacts Form-C
  - h. Terminal block: incoming power
  - i. Terminal block: float switches
  - j. Option: adjustable seal failure circuits and red LED indicators (must select option 5E when ordering)
7. Ground lugs
8. Red LED beacon provides 360° visual check of alarm condition
9. Alarm horn provides audible alarm warning (83 to 85 decibel rating)
10. Exterior alarm Test/Normal/Silence switch allows horn and light to be tested and horn to be silenced in an alarm condition; alarm automatically resets once alarm condition is cleared

Model 324 control panels cannot be returned. Please refer to the Product Return section.

**Note: Other options available. Options selected may increase enclosure size and change component layout.**

**Note: Schematic/Wiring Diagram and Pump Specification Label are located inside the panel.**



**MODEL 324 - Three phase, duplex pump control with intrinsically safe circuits.**

<b>324</b> CONTROL PANEL	ALARM PACKAGE	<b>W</b> ENCLOSURE RATING	PUMP FULL LOAD AMPS	LEVEL CONTROL APPLICATION	<b>6A10E19B</b> OPTIONS (LISTED BELOW)
-----------------------------	---------------	------------------------------	---------------------	---------------------------	---

<b>CONTROL PANEL</b>	✓	324	Three Phase Duplex Intrinsically Safe	\$4,578.35
<b>ALARM PACKAGE</b>		0	Select Options or No Alarm Package	- \$40.17
		1	Alarm Package (includes test/normal/silence switch, red light, & horn)	Base
<b>ENCLOSURE RATING</b>	✓	W	Weatherproof, NEMA 4X (engineered thermoplastic)	Base
<b>PUMP FULL LOAD AMPS</b>			208/240/480V	600V
		001	1.0 - 1.6 FLA	005 1.0 - 1.6 FLA Base
		101	1.6 - 2.5 FLA	105 1.6 - 2.5 FLA Base
		201	2.5 - 4.0 FLA	205 2.5 - 4.0 FLA Base
		301	4.0 - 6.3 FLA	305 4.0 - 6.3 FLA Base
		401	6.0 - 10.0 FLA	405 6.0 - 10.0 FLA Base
		511	9.0 - 14.0 FLA	515 9.0 - 14.0 FLA \$86.52
		611	13.0 - 18.0 FLA	615 13.0 - 18.0 FLA \$86.52
		621	17.0 - 23.0 FLA	625 17.0 - 23.0 FLA \$114.33
		701	20.0 - 25.0 FLA	705 20.0 - 25.0 FLA \$114.33
<b>LEVEL CONTROL APPLICATION</b>		H	Floats - Pump Down (select Option 17 below)	See Options
		L	Floats - Pump Up (select Option 17 below)	See Options
		E	EZconnex® Float Switch System	See Options
		X	No Floats	Base

**PRICING WORKSHEET**

<b>Model 324 Base Price</b>	<b>\$4,578.35</b>
Alarm Package	_____
Enclosure Rating	_____
Pump Full Load Amps	_____
Level Control Application	_____
Total Options	_____
<b>TOTAL LIST PRICE</b>	_____

OPTIONS	DESCRIPTION	LIST PRICE
4A	Redundant Off (must also select Option 4D if floats are required)	\$309.00
4B	Red Redundant Off Indicator & Alarm (must also select Option 4A)	\$87.55
4D	Redundant Off Float (must also select Option 4A and Option 17)	\$40.17
5A	Thermal Cutout/Heat Sensor Auto Reset (for pumps with thermal switch leads)	\$133.90
5E	Seal Failure Circuit & Red Indicator (2 wire)	\$255.44
✓ 6A	<b>Auxiliary Alarm Contact, Form C (included as standard)</b>	<b>\$0.00</b>
6G	Auxiliary Contact, Dry, Seal Fail, Normally Open (must select Option 5E)	\$216.30
8A	Elapsed Time Meter	\$149.35
8C	Event (Cycle) Counter	\$123.60
10A	Clear Inner Swing-Out Door with Dead Front (lights and switches mounted on inner door) <b>PANELS ORDERED WITH THIS OPTION CANNOT BE RETURNED</b>	\$309.00
✓ 10E	<b>Lockable Latch - NEMA 4X (included as standard, must select Enclosure Rating W above)</b>	<b>\$0.00</b>
10G	Lightning Arrestor	\$309.00
10K	Anti-condensation Heater	\$149.35

OPTIONS	DESCRIPTION	LIST PRICE
14B	Main Disconnect (rotary style, mounted through door, non-fused, padlockable in the OFF position, door interlock in the ON-position)	0-20 FLA (total of both pumps) \$515.00 20-50 FLA (total of both pumps) \$592.25
16C	30' Cord in Lieu of 20' Cord (per float)	\$8.24
16D	40' Cord in Lieu of 20' Cord (per float)	\$16.48
17C	Sensor Float® / Internally Weighted (3 Floats) - Mercury	\$170.10
17D	Sensor Float® / Externally Weighted (3 Floats) - Mercury	\$176.40
17G	SJE MilliAmpMaster™ / Pipe Clamp (3 Floats) - Mechanical	\$120.51
17H	SJE MilliAmpMaster™ / Externally Weighted (3 Floats) - Mechanical	\$148.32
17J	Sensor Float® / Pipe Clamp (3 Floats) - Mercury	\$144.90
✓ 19B	<b>Lead Lag Selector Switch (included as standard)</b>	<b>\$0.00</b>
19F	Fourth Float to Separate Alarm Function from Lag	\$40.17
19T	TOA (Test/Off/Automatic) Switches and Pump Run Lights Through Door Mounted	\$216.30
19U	HOA (Hand/Off/Automatic) Switches and Pump Run Lights Through Door Mounted	\$216.30
19X	Door Mounted Pump Run Indicator	\$216.30
33D	EZconnex® 3-Port, 25', with 10' Floats (3) / Pipe Clamp	\$350.27
35D	EZconnex® 4-Port, 25', with 10' Floats (4) / Pipe Clamp	\$424.73

For additional control panel options, please contact Technical Support at techsupport@sjinc.com.

Intrinsically Safe

California Prop 65 requires the following: ⚠️ WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov