SENSOR FLOAT® CONTROL SWITCH

Mercury-Activated, Narrow-Angle Float Switch Designed to Activate Pump Control Panels and Alarms

The Sensor Float® mercury-activated, narrow-angle control switch is designed to accurately monitor liquid levels and activate control pump control panels and alarms in:

- non-potable water applications
- sewage applications

The Sensor Float® control switch is not sensitive to rotation and is suitable for use with intrinsically safe circuits. Contact SJE Rhombus regarding specific intrinsically safe applications.

Normally Open Model (high level)
The control switch turns on (closes) when the switch tips slightly **above** horizontal signaling a high level, and turns off (opens) when the switch drops slightly below horizontal.

Normally Closed Model (low level)
The control switch turns on (closes) when the switch drops slightly **below** horizontal signaling a low level, and turns off (opens) when the switch tips slightly above horizontal.



UL Listed for Water & Sewage

LISTED 83N2 LR54245

FEATURES

- Suitable for use with intrinsically safe circuits
- Not sensitive to rotation
- Control differential of .5 inches (1 cm) above or below horizontal

OPTIONS

This switch is available:

- for normally open (high level) applications or normally closed (low level) applications
- in standard cable lengths of 10, 15, 20, or 30 feet and 3, 5, 6, or 10 meters (longer lengths available)
- with three mounting options that allow for flexibility in installation:

  Mounting Clamp: for applications where the switch can be attached to a discharge pipe or similar mounting device

  Internally Weighted: for applications where the switch can be suspended from above

  Externally Weighted: for applications where the switch can be suspended from above

SJE RHOMBUS®
Powered by SJE

9500119N-WEB Rev 07/26
© 2020 SJE, Inc. All Rights Reserved.
SJE Rhombus is a trademark of SJE, Inc.

SENSOR FLOAT® CONTROL SWITCH - Mercury-activated, narrow-angle float switch designed to activate pump control panels and alarms.

NORMALLY OPEN		NORMALLY CLOSED			
Part #	Description	Part #	Description	Shipping Weight	List Price
1002108	10PCNO	**1002111**	10PCNC	1.29 lbs.	$89.30
1002072	10SWINO	**1002075**	10SWINC	1.85 lbs.	$95.92
1002143	10SWENO	**1002146**	10SWENC	2.66 lbs.	$105.84
1002117	15PCNO	**1002120**	15PCNC	1.64 lbs.	$95.92
1002080	15SWINO	**1002083**	15SWINC	2.22 lbs.	$102.53
1002152	15SWENO	**1002155**	15SWENC	2.90 lbs.	$112.46
1002125	20PCNO	**1002128**	20PCNC	1.99 lbs.	$102.53
1002089	20SWINO	**1002092**	20SWINC	2.59 lbs.	$109.15
1002161	20SWENO	**1002164**	20SWENC	3.27 lbs.	$119.07
1002134	30PCNO	**1002137**	30PCNC	2.13 lbs.	$117.97
1002098	30SWINO	**1002101**	30SWINC	3.28 lbs.	$124.58
1002170	30SWENO	**1002173**	30SWENC	3.88 lbs.	$134.51

PC = **P**ipe **C**lamp **WI** = **W**eighted **I**nternally **WE** = **W**eighted **E**xternally **NO** = **N**ormally **O**pen **NC** = **N**ormally **C**losed

NOTE: Descriptions are grouped by cable length measured in feet (10, 15, 20, 30).

PACKAGING: Bagged - Standard

ADDITIONAL CABLE: Longer cable lengths available.

SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE) jacket

FLOAT: 3.38 inch diameter x 4.55 inch long (8.58 cm x 11.56 cm), high impact, corrosion resistant, PVC housing for use in sewage and non-potable water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

MERCURY SWITCH: single pole, single throw, mercury-to-mercury contacts, hermetically sealed in a steel capsule and epoxy sealed in the float housing

ELECTRICAL: 5 amp 120/230 VAC, 50/60 Hz

NOTE: Suitable for use with intrinsically safe circuits.

Contact SJE Rhombus regarding specific intrinsically safe applications.

OTHER INFORMATION

NORMALLY OPEN (HIGH LEVEL) OPERATION
The control switch closes (turns on) when the float tips slightly **above** horizontal signaling a high level, and opens (turns off) when the float drops slightly **below** normal.

NORMALLY CLOSED (LOW LEVEL) OPERATION
The control switch closes (turns on) when the float drops slightly **below** horizontal signaling a low level, and opens (turns off) when the float tips slightly **above** horizontal.

California Prop 65 requires the following: ⚠ WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov