
INSTALLER FRIENDLY SERIES® (IFS)
THREE PHASE DUPLEX

Demand Dose or Timed Dose, Float, Sensor or Transmitter Controlled System for Pump Control and System Monitoring



c UL us LISTED

Panel layout may vary with options.
Reg. Cdn Pat. & TM Off
US Patent No. 8,336,385; 8,567,242; 8,650,949

Connects to PANEL LINK

The Next Generation IFS duplex control panel utilizes an innovative circuit board design enclosed in a touch-safe housing to control two 208/240/480 and 600 VAC three phase pumps in water and sewage applications. These newly redesigned IFS panels feature an easy-to use color LCD interface located on the inner door for programming and system monitoring. The panel configuration can be easily converted in the field to either a timed dose or demand dose through the LCD interface.

The panel can easily be changed in the field to utilize floats, Sub-X™ LT Transmitter or the C-Level™ Sensor for continuous level monitoring. The Sub-X™ LT Transmitter and the C-Level™ Sensor sense the level in the tank and sends a signal to the panel. Pump activation levels can be adjusted by using the LCD interface.

- **Panel Link Puck ready (self-connecting cellular device for remote monitoring)**

LCD INTERFACE FEATURES

- Full color graphics and menu navigation encoder for easy setup
- Touch safe housing
- Pump Hand/Off/Auto Control selectable via menu navigation
- Sub-X™ LT Transmitter, C-Level™ Sensor or float operation selectable
- Demand or Timed Dose operation selectable via menu navigation
- Tank Level Indication and setpoint monitoring at-a-glance
- Lead pump is easily identified by a graphic ring around the current lead pump regardless of control mode (timed dose or demand)
- Displays remaining time in Timed Dose mode
- RJ45 communication connector
- Flashing function for alarm beacon and horn (configurable)
- Manual alarm reset (configurable)
- Thermal cutout and seal failure module (optional)

SJE RHOMBUS®
Powered by SJE

COMPONENTS

1. Enclosure base measures 16 x 14 x 6 inches (40.64 x 35.56 x 15.24 cm); NEMA 4X (ultraviolet stabilized thermoplastic)
2. Red Alarm Beacon provides 360° visual check of alarm condition
3. Motor protective switches provide adjustable overload, branch circuit protection and pump disconnect
4. IEC motor contactors control pumps by switching electrical lines
5. Multi-tap transformer (208/240/480 VAC primary) provides 120 VAC control alarm voltage or 600 VAC primary transformer
6. Sub-X™ LT Transmitter, C-Level™ Sensor and float connection terminal blocks
7. Controller Features:
   a. Incoming Control/Alarm Power terminal blocks
   b. Control/Alarm Power/System Status green LED indicators illuminate if control/alarm power is present and controller is operating*
   c. Controller status green LED indicators for: Power/Active, Float Input Status, Pump Run, C-Level Active*
   d. Normally open auxiliary alarm contacts included as standard
   e. Control Power On/Off switch
   f. Green LED Pump Run indicators illuminate when pump is called to run*
   g. Control panel able to operate if LCD interface fails or is disconnected
   h. Touch safe housing
8. Panel Link Puck (optional - see Panel Link Puck catalog page for additional details)
9. Modbus Expansion Port (RJ45)
9. Option 5AE - Thermal Cutout/Heat Sensor & Seal Failure Module
10. Large incoming power connection terminal block
11. Alarm Horn provides warning of alarm condition (Not shown)
13. Exterior Alarm Test/Silence - alarm automatically resets once alarm condition is cleared (Not shown)

- Five-year limited warranty on panel
- Two-year limited warranty on C-Level™ Sensor and Sub-X™ LT Transmitter

*In fault condition, LED indicators will be red.

Note: Options, voltage, and amp range selected may change enclosure size and component layout.

Note: Schematic/Wiring Diagram and Pump Specification Label are located inside the panel.

9500056U-WEB Rev 07/26
© 2020 SJE, Inc. All Rights Reserved.
SJE Rhombus is a trademark of SJE, Inc.

INSTALLER FRIENDLY SERIES® THREE PHASE DUPLEX - Demand or timed dose system for pump control and system monitoring.

IFN	6	1	W			6A8AC10E
CONTROL PANEL	MODEL TYPE	ALARM PACKAGE	ENCLOSURE RATING	PUMP FULL LOAD AMPS	LEVEL CONTROL APPLICATION	OPTIONS (LISTED BELOW)

CONTROL PANEL	✓	IFN					
MODEL TYPE	✓	6	Three Phase Duplex (includes Option 6A, 8AC and 10E as standard)				$3,102.36
ALARM PACKAGE	✓	1	Alarm Package (includes test/silence switch, red light, & horn)				Base
ENCLOSURE RATING	✓	W	Weatherproof, NEMA 4X (engineered thermoplastic)				Base
PUMP FULL LOAD AMPS			208/240/480V			600V	
		001	1.0 - 1.6 FLA		005	1.0 - 1.6 FLA	Base
		101	1.6 - 2.5 FLA		105	1.6 - 2.5 FLA	Base
		201	2.5 - 4.0 FLA		205	2.5 - 4.0 FLA	Base
		301	4.0 - 6.3 FLA		305	4.0 - 6.3 FLA	Base
		401	6.0 - 10.0 FLA		405	6.0 - 10.0 FLA	Base
		511	9.0 - 14.0 FLA		515	9.0 - 14.0 FLA	$86.52
		611	13.0 - 18.0 FLA		615	13.0 - 18.0 FLA	$86.52
		621	17.0 - 23.0 FLA		625	17.0 - 23.0 FLA	$114.33
		701	20.0 - 25.0 FLA		705	20.0 - 25.0 FLA	$114.33
LEVEL CONTROL APPLICATION		H	Floats - Pump Down (select Option 17 below) Timed dose = redundant off, timer enable, alarm / Demand dose = stop, start, alarm (all systems will ship with 3 floats by default)				See Options
		E	EZconnex® Float Switch System				See Options
		X	No Floats, Transmitter or Sensor				Base
		C	C-Level™ Sensor (select Option 24 or 29)* Select Option 3E and/or 4D for high water alarm and/or redundant off floats				See Options
		T	Sub-X™ LT Transmitter (select Option 31).* Select Option 3E and/or 4D for high water alarm and/or redundant off floats.				See Options

PRICING WORKSHEET

IFS Three Phase Duplex Base Price	**$3,102.36**
Alarm Package	
Enclosure Rating	
Pump Full Load Amps	
Level Control Application	
Total Options	
TOTAL LIST PRICE	

***NOTE:** When using the Sub-X™ LT Transmitter or C-Level™ Sensor: Operation is for Pump down applications only.
Industry practices suggest that a secondary device, such as a float switch, be used for redundant activation of the high level alarm and pump shut off.

	OPTIONS	DESCRIPTION	LIST PRICE
	3E	High Water Alarm Float (must also select Option 17)** **Only Available with Level Control Application = C or T**	$40.17
	4D	Redundant Off Float (must also select Option 17)** **Only Available with Level Control Application = C or T**	$40.17
	5AE	Thermal Cutout/Heat Sensor & Seal Failure Circuit (2 wire)	$322.39
✓	**6A**	**Auxiliary Alarm Contact, Form A (included as standard)**	**$0.00**
✓	**8AC**	**Display Board - Includes: ETM Counter, Events (Cycles) Counter, Alarm Counter, and Override Counter (Timed Dose Only) (included as standard)**	**$0.00**
✓	**10E**	**Lockable Latch - NEMA 4X (included as standard)**	**$0.00**
	10G	Lightning Arrestor	$309.00
	10K	Anti-condensation Heater	$149.35
	16C	30' Cord in Lieu of 20' Cord (per Float)	$8.24
	16D	40' Cord in Lieu of 20' Cord (per Float)	$16.48
	16E	50' Cord in Lieu of 20' Cord (per Float)	$24.72
	16G	100' Cord in Lieu of 20 Cord (per Float)	$65.92
	17C	Sensor Float® / Internally Weighted (3 Floats) - Mercury**	$170.10
	17D	Sensor Float® / Externally Weighted (3 Floats) - Mercury**	$176.40

****When selecting options 3E and 4D, you must also select an option 17 to indicate the type of float needed. There is no additional charge for the 17 option.**

	OPTIONS	DESCRIPTION	LIST PRICE
	17G	SJE MilliAmpMaster™ / Pipe Clamp (3 Floats) - Mechanical**	$120.51
	17H	SJE MilliAmpMaster™ / Externally Weighted (3 Floats) - Mechanical**	$148.32
	17J	Sensor Float® / Pipe Clamp (3 Floats) - Mercury**	$144.90
	19F	4th Float for Timer Override **Only Available with Level Control Application = H**	$40.17
	24E	C-Level™ CL40 Sensor with 25' Vented Cable	$341.25
	24F	C-Level™ CL40 Sensor with 50' Vented Cable	$393.75
	24P	C-Level™ CL40 Sensor with 100' Vented Cable	$498.75
	29A	C-Level™ CL100 Sensor with 25' Vented Cable	$393.75
	29B	C-Level™ CL100 Sensor with 50' Vented Cable	$393.75
	29C	C-Level™ CL100 Sensor with 100' Vented Cable	$498.75
	31A	Sub-X™ LT Transmitter 25' (4-20mA)	$334.75
	31B	Sub-X™ LT Transmitter 50' (4-20mA)	$386.25
	31C	Sub-X™ LT Transmitter 100' (4-20mA)	$489.25
	33D	EZconnex® 3-Port, 25', with 10' Floats (3) / Pipe Clamp	$350.27
	35D	EZconnex® 4-Port, 25', with 10' Floats (4) / Pipe Clamp	$424.73
		CONNECT THIS PANEL TO THE CLOUD	
	27X	Panel Link Puck***	$395.00

*****Panel Link Puck requires a subscription.**
See Panel Link Puck catalog page for additional details.

For additional level control and control panel options, please contact Technical Support at techsupport@sjeinc.com.

Note: Added options, voltage, and amp range selected may change enclosure size and enclosure features, and component layout. Schematic/Wiring Diagram and Pump Specification Label are located inside the panel.

SENSOR/TRANSMITTER	OPERATING RANGE
C-Level™ CL40	0-39.9 inWC
C-Level™ CL100	0-99.9 inWC
Sub-X™ LT Transmitter (4-20mA)	0-100 inWC

California Prop 65 requires the following: ⚠ WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov